

MixMix

Manual 2022


visplay

play it smart



MixMix consists of aluminium profiles with a wave effect. Due to the special shape of the profile, the merchandise support adapter is concealed in a shadow joint. MixMix can be infinitely expanded both horizontally and vertically, and used as a striking brand element. Designed for small items, the profile offers versatile display options: in gondolas, as entire wall panels and on a suspended panel in front of the wall. Merchandise supports are hooked into the profile and can be repositioned anywhere along its length as required – for a personalised layout. A MixMix profile can also be mounted in wooden panels.

MixMix profile
single-sided






End profile
single-sided top



Universal support bracket



Dimensions



Characteristics

- ⓘ Observe the assembly and operating instruction
- Weight 10 kg per 1000 mm

- Is fitted on the MixMix single-sided profile.
- ⓘ Observe the assembly and operating instruction

- For decorative panels or acrylglass boxes.
- Max. weight load = 2 kg per adapter

Order number


natural anodised aluminium	
3100 mm	334-789.05
lto 250-3100 mm	334-790.05

End profile must be ordered separately.

natural anodised aluminium	
3100 mm	334-791.05
lto 250-3100 mm	334-792.05

plastic semi-transparent	
	981-287.02



Front arm, straight Ø 8 mm



Max. weight load = 4 kg

chrome / plastic semi-transparent	
100 mm	395-201.42
200 mm	395-202.42
300 mm	395-203.42
silk / plastic semi-transparent	
100 mm	395-201.32
200 mm	395-202.32
300 mm	395-203.32



Hanging frame Ø 15 mm



Max. weight load = 8 kg

chrome / plastic semi-transparent	
	395-206.42
silk / plastic semi-transparent	
	395-206.32



Hook, straight Ø 6 mm



Max. weight load = 1 kg

chrome / plastic semi-transparent	
100 mm	984-510.42
150 mm	984-511.42
200 mm	984-512.42
250 mm	984-513.42



Looped hook Ø 4 mm



Max. weight load = 3 kg

chrome / plastic semi-transparent	
150 mm	984-508.42
200 mm	984-509.42


Eyewear holder Ø 4 mm



Max. weight load = 1 kg

chrome / plastic semi-transparent
984-582.42

Shelf profile




For shelves 6 mm in thickness.

Max. weight load = 10 kg


📄 Drawing no.
289-876 Glass shelf 6 mm

natural anodised aluminium
l to 50–3100 mm **334-839.05**

Sliss



100 x



Prevents scratches on hanging rails and front arms in silk or stainless steel.

To clip into coat hanger hook (Ø 3.4–3.8 mm).

transparent
929-449.02

Set of 100 pcs.

Standard surface finishes for basic system



natural anodised aluminium

Standard surface finishes for merchandise supports



silk



chrome

ISO 9001 / ISO 14001

The safety of Visplay products is continuously monitored by external testing institutes, Intertek Germany and UL (Underwriters Laboratories Inc.).

For electrified systems, the CE marking confirms conformity with the relevant directives.

All processes in our company are subject to a comprehensive management system which corresponds with the ISO 9001 quality standard and the ISO 14001 environment standard.

Copyright ©

All products by Visplay and their names are protected by intellectual property rights. This protection is valid for the basic system along with the merchandise supports and accessories.

In the event of infringement, Visplay reserves the right to take legal steps.

- Our general conditions of delivery and sale are valid for all orders.
- We reserve the right to make technical and formal alterations.



All dimensions are given in millimetres.

lto = Length to order

hto = Height to order

cto = Colour to order

L = Length

A = Axis

H = Height

T = Depth

Quick delivery program

The following symbols which appear on the left-hand side near the part number indicate the delivery time for each individual item:

- = Delivery time: up to 5 working days ex works Weil am Rhein, Germany
- ⊙ = Delivery time: up to 10 working days ex works Weil am Rhein, Germany

All other items on request.

Longer delivery times may occur in the event of exceptionally strong demand.

Air freight

Items which are to be dispatched by air must not exceed a total length of 3 metres.

📄 Drawings of wooden and glass shelves

Production drawings of shelves with the 6 digit part number are available for download in the product area and in the download centre at www.visplay.com or can be received on request.

📖 Assembly and operating instructions

Special assembly and operating instructions exist for all products by Visplay in order to guarantee the functions and safety. These instructions contain important information e.g. maximum weight loads, assembly dimensions or information on the correct assembly and use. The respective assembly and operating instructions are included in the delivery of our systems. A general catalogue is also available on request for planning purposes. The assembly and operating instructions are available for download in the product area and in the download centre at www.visplay.com.

You can get in touch with us by email or by phone.
Contact details for our offices can be found here:
www.visplay.com/contact

visplay

www.visplay.com info@visplay.com